

Hex Couplings

PCG



Female NPT Threads

P-NPT Size	Ps-NPT Size	Basic Ordering Number	Dimension, mm			Working Pressure psig (bar)	
			L	F	E	316 SS, Steel	Brass
1/16	1/16	-PCG-HT1	19.8	11.1	4.8	6700 (460)	3300 (227)
1/8	1/8	-PCG-HT2	29.6	14.3	8.6	6500 (447)	3200 (220)
1/4	1/8	-PCG-HT4-HT2	31.0	19.1	8.6	6600 (454)	3300 (227)
1/4	1/4	-PCG-HT4	30.2	19.1	11.4	6600 (454)	3300 (227)
3/8	1/4	-PCG-HT6-HT4	35.1	22.2	11.4	5300 (365)	2600 (179)
3/8	3/8	-PCG-HT6	33.3	22.2	15.0	5300 (365)	2600 (179)
1/2	1/8	-PCG-HT8-HT2	39.6	27.0	8.6	4800 (337)	2400 (165)
1/2	1/4	-PCG-HT8-HT4	44.4	27.0	11.4	4800 (337)	2400 (165)
1/2	3/8	-PCG-HT8-HT6	45.2	27.0	15.0	4800 (337)	2400 (165)
1/2	1/2	-PCG-HT8	39.6	27.0	18.5	4800 (337)	2400 (165)
3/4	1/4	-PCG-HT12-HT4	46.0	33.3	11.4	4600 (316)	2300 (158)
3/4	1/2	-PCG-HT12-HT6	52.3	33.3	18.5	4600 (316)	2300 (158)
3/4	3/4	-PCG-HT12	41.1	33.3	21.9	4600 (316)	2300 (158)
1	1/2	-PCG-HT16-HT8	55.6	41.3	18.5	4400 (303)	2200 (151)
1	3/4	-PCG-HT16-HT12	57.2	41.3	21.9	4400 (303)	2200 (151)
1	1	-PCG-HT16	50.8	41.3	25.7	4400 (303)	2200 (151)